

<b>Gas Saver Model:</b>	<b>Standard</b>	<b>SE-II</b>
Gas Control System	Diaphragm	Solenoid Valve
Gas Flow Control System	N/A	N/A
Ignition	Spark rod	Pilot flame
Flame Detection	N/A	Flame Sensor rod
Flammable Gas	Acetylene,LPG	Acetylene,LPG,LNG
Gas Connection	Oxygen:M16x1.5 right (With D=8 mm. Hose nipple) Flammable Gas(Ember Gas):M16x1.5 left (With D=9 mm. Hose nipple)	
Pressure Resistant	- -	Max 0.7 Mpa (Oxygen) Max 0.4 Mpa (Flammable gas)
Weight	Approx 2.5 kg.	Approx 4 kg.
Optional	Fash back unit	N <sub>2</sub> control unit Mixer control unit Fash back unit
Power supply	N/A	220VAC (110VAC for Japan)

<b>STANDARD AND SE-II GAS SAVER COMPARE</b>		
Pilot flame gas (g./min)	1.98	-
LPG. Gas Cost (THB/L))	12.50	-
Operation time (Hour) /day	10	10
Working (day) / month	25	25
Pilot flame gas Cost. (THB/M.)	<b>735.08</b>	-
Electric power (Watts)	-	30.00
(kWh)/day	-	0.30
(kWh)/month	-	7.50
Electric Cost.(Bath)/unit	-	3.00
Electric Cost. total (THB/M.)	-	<b>22.50</b>